

Page 1/8

## Safety data sheet according to 1907/2006/EC, as ammended by Regulation (EU) no. 2015/830

Printing date 07.12.2020 Version: 1.1 Revision: 07.12.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: WATERCOLOUR VARNISH MATT 050
- · Article number: 24285050
- · UFI: XN10-D0A3-300H-8421
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use: Picture varnish

· 1.3 Manufacturer/Supplier:

Royal Talens P.O.Box 4

NL-7300 AA Apeldoorn Tel. +31 (0)55 5274700

Further information obtainable from:

Regulatory Affairs safety@royaltalens.com

· 1.4 Emergency telephone number:

Great Britain: National Poisons Information Service (Birmingham) tel. (44) (0) 1215074123

Ireland: National Poisons Information Centre (Dublin) tel. 35 3 18379966

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

GHS09

(Contd. on page 2)

Printing date 07.12.2020 Version: 1.1 Revision: 07.12.2020

(Contd. of page 1)

### · Signal word Danger

### · Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P501 Dispose of contents/container to hazardous waste collection point.

### · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with non-hazardous additions.

· Dangerous components:		
EC/List number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	30-50%
	🚸 Flam. Liq. 3, H226; 🗞 Asp. Tox. 1, H304; 🕦 STOT SE 3, H336	
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	25-30%
Reg.nr.: 01-2119473851-33	♦ Flam. Liq. 2, H225; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H336	
	Hydrocarbons, C9, aromatics	5-10%
EC/List number: 918-668-5 Reg.nr.: 01-2119455851-35	♠ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335-H336	

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed May cause drowsiness or dizziness.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water spray
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases/vapours is possible during heating or in case of fire.

(Contd. on page 3)

Printing date 07.12.2020 Version: 1.1 Revision: 07.12.2020

(Contd. of page 2)

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

*Ensure adequate ventilation* 

Keep away from ignition sources.

- 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- · Storage class: -
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

	s with limit values that require monitoring a	
	oons, C7-C9, n-alkanes, isoalkanes, cyclics (	25-30%)
TWA Long	g-term value: 1000 mg/m³, 200 ppm	
DNELs		
Hydrocarb	oons, C9-C11, n-alkanes, isoalkanes, cyclics,	<2% aromatics
Oral	DNEL,long term (chronic) - systemic effects	125 mg/kg bw/day (Consumer)
Dermal	DNEL,long term (chronic) - systemic effects	125 mg/kg bw/day (Consumer)
		208 mg/kg bw/day (Employee)
Inhalative	DNEL,long term (chronic) - systemic effects	185 mg/m3 (Consumer)
		871 mg/m3 (Employee)
Hydrocarb	oons, C7-C9, n-alkanes, isoalkanes, cyclics	
Oral	DNEL,long term (chronic) - systemic effects	699 mg/kg bw/day (Consumer)
Dermal	DNEL,long term (chronic) - systemic effects	699 mg/kg bw/day (Consumer)
		773 mg/kg bw/day (Employee)
		(Contd. on pa

Printing date 07.12.2020 Version: 1.1 Revision: 07.12.2020

		(Contd. of page 3)
Inhalative	DNEL,long term (chronic) - systemic effects	608 mg/m3 (Consumer)
		2,035 mg/m3 (Employee)
64742-95-	6 Hydrocarbons, C9, aromatics	
	DNEL,long term (chronic) - systemic effects	
Dermal	DNEL,long term (chronic) - systemic effects	
		25 mg/kg bw/day (Employee)
Inhalative	DNEL,long term (chronic) - systemic effects	
		150 mg/m3 (Employee)

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Respiratory protection:

Not necessary if room is well-ventilated.

Only during spraying without adequate removal by suction.

Protection of hands:



If prolonged or repeated contact is likely, chemical resistant gloves are recommended.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses if risk of splashes.

## SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid

Colour: According to product specification

· Odour: Characteristic

· pH-value: Not applicable.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: Undetermined.

· Flash point: 1 °C

· Flammability (solid, gas): Not applicable.

• **Decomposition temperature:** Not determined.

• Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

(Contd. on page 5)

Printing date 07.12.2020 Version: 1.1 Revision: 07.12.2020

		(Contd. of page
· Explosion limits:		
· Upper:		
Oxidising properties	No further relevant information available.	
· Vapour pressure:	Not determined.	
Density at 20 °C:	$0.82 \text{ g/cm}^3$	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic at 40 °C:	$>20.5 \text{ mm}^2/\text{s}$	
9.2 Other information	No further relevant information available.	

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable under recommended storage and handling conditions (see section 7).
- · 10.3 Possibility of hazardous reactions

Dangerous reactions are not expected if the product is handled according to its intended use.

- · 10.4 Conditions to avoid Keep away from sources of ignition No smoking.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No decomposition if used according to specifications.

### SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:			
Hydrocarb	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics			
Oral	LD50	>5,000 mg/kg (rat)		
Dermal	LD50	>5,000 mg/kg (rabbit)		
Inhalative	LC50/4 h	>5,000 mg/l (rat)		
Hydrocarb	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			
Oral	LD50	>5,000 mg/kg (rat)		
Dermal	LD50	>2,000 mg/kg (rat)		
Inhalative	LC50/4 h	>20 mg/l (rat)		
64742-95-	64742-95-6 Hydrocarbons, C9, aromatics			
Oral	LD50	2,000-5,000 mg/kg (rat)		
Dermal	LD50	>2,000 mg/kg (rabbit)		

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 07.12.2020 Version: 1.1 Revision: 07.12.2020

(Contd. of page 5)

- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

### 64742-95-6 Hydrocarbons, C9, aromatics

EC50, acute 1-10 mg/l (algae)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

## **SECTION 14: Transport information**

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN1263

· 14.2 UN proper shipping name

ADR 1263 PAINT,

ENVIRONMENTALLY HAZARDOUS

· **IMDG, IATA** PAINT

- · 14.3 Transport hazard class(es)
- $\cdot$  ADR





· Class 3 Flammable liquids.

(Contd. on page 7)

Printing date 07.12.2020 Version: 1.1 Revision: 07.12.2020

	(Contd. of page
· Label	3
· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	None.
· ADR	III
· 14.5 Environmental hazards:	
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	33 F. F. G. F.
· EMS Number:	F-E, <u>S-E</u>
· 14.7 Transport in bulk according to Annex II o	
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IIN IIM a dal Danidation II.	
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, II ENVIRONMENTALLY HAZARDOUS

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 8)

Printing date 07.12.2020 Version: 1.1 Revision: 07.12.2020

(Contd. of page 7)

### · Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

- GB