

**Safety data sheet**  
according to 1907/2006/EC, as ammended by Regulation (EU) no.  
2015/830

Printing date 25.11.2020

Version: 1.1

Revision: 25.11.2020

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name:** - TALENS ACRYLIC VARNISH MATT 115, aerosol  
- AMSTERDAM ACRYLIC VARNISH MATT 115, aerosol
- **Article number:** 95165115; 95168115
- **UFI:** M440-20AK-Y00V-F0XW
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
Relevant identified use: Picture varnish
- **1.3 Manufacturer/Supplier:**  
Royal Talens  
P.O.Box 4  
NL-7300 AA Apeldoorn Tel. +31 (0)55 5274700
- **Further information obtainable from:**  
Regulatory Affairs  
safety@royaltalens.com
- **1.4 Emergency telephone number:**  
Great Britain: National Poisons Information Service (Birmingham) tel. (44) (0) 1215074123  
Ireland: National Poisons Information Centre (Dublin) tel. 35 3 18379966

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1      H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

STOT SE 3      H336      May cause drowsiness or dizziness.

Aquatic Chronic 3 H412      Harmful to aquatic life with long lasting effects.

- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Danger

(Contd. on page 2)

GB

**Safety data sheet**  
according to 1907/2006/EC, as amended by Regulation (EU) no.  
2015/830

Printing date 25.11.2020

Version: 1.0

Revision: 25.11.2020

(Contd. of page 1)

- **Hazard-determining components of labelling:**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

- **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container to hazardous waste collection point.

- **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with non-hazardous additions.

- **Dangerous components:**

EC/List number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336	30-50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-20%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane, pure ⚠ Flam. Gas 1A, H220; ⚠ Acute Tox. 3, H331; Press. Gas (Comp.), H280	10-20%
CAS: 64742-95-6 EC/List number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	5-10%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	2.5-5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

- **After eye contact:** Rinse opened eye for several minutes under running water.

- **After swallowing:** If symptoms persist consult doctor.

- **4.2 Most important symptoms and effects, both acute and delayed** May cause drowsiness or dizziness.

(Contd. on page 3)

**Safety data sheet**  
 according to 1907/2006/EC, as ammended by Regulation (EU) no.  
 2015/830

Printing date 25.11.2020

Version: 1.0

Revision: 25.11.2020

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**  
 No further relevant information available.

### **SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

### **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
 Keep away from ignition sources.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.
- **6.3 Methods and material for containment and cleaning up:**  
 Ensure adequate ventilation.  
 Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**  
 See Section 7 for information on safe handling.  
 See Section 8 for information on personal protection equipment.  
 See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
 Ensure good ventilation/exhaustion at the workplace.  
 Open and handle receptacle with care.
- **Information about fire - and explosion protection:**  
 Do not spray onto a naked flame or any incandescent material.  
 Keep ignition sources away - Do not smoke.  
 Protect from heat.  
 Protect against electrostatic charges.  
 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
 Store in a cool location.  
 Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
 Do not seal receptacle gas tight.  
 Store in cool, dry conditions in well sealed receptacles.  
 Protect from heat and direct sunlight.
- **Storage class:** -
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, as amended by Regulation (EU) no.  
2015/830

Printing date 25.11.2020

Version: 1.0

Revision: 25.11.2020

(Contd. of page 3)

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

##### · Ingredients with limit values that require monitoring at the workplace:

###### 106-97-8 butane, pure (10-20%)

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm  
Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm  
Carc (if more than 0.1% of buta-1.3-diene)

###### 67-63-0 propan-2-ol (2.5-5%)

WEL Short-term value: 1250 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 999 mg/m<sup>3</sup>, 400 ppm

#### · DNELs

##### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral	DNEL, long term (chronic) - systemic effects	125 mg/kg bw/day (Consumer)
Dermal	DNEL, long term (chronic) - systemic effects	125 mg/kg bw/day (Consumer) 208 mg/kg bw/day (Employee)
Inhalative	DNEL, long term (chronic) - systemic effects	185 mg/m <sup>3</sup> (Consumer) 871 mg/m <sup>3</sup> (Employee)

##### 64742-95-6 Hydrocarbons, C9, aromatics

Oral	DNEL, long term (chronic) - systemic effects	11 mg/kg bw/day (Consumer)
Dermal	DNEL, long term (chronic) - systemic effects	11 mg/kg bw/day (Consumer) 25 mg/kg bw/day (Employee)
Inhalative	DNEL, long term (chronic) - systemic effects	32 mg/m <sup>3</sup> (Consumer) 150 mg/m <sup>3</sup> (Employee)

##### 67-63-0 propan-2-ol

Oral	DNEL, long term (chronic) - systemic effects	26 mg/kg bw/day (Consumer)
Dermal	DNEL, long term (chronic) - systemic effects	319 mg/kg bw/day (Consumer) 888 mg/kg bw/day (Employee)
Inhalative	DNEL, long term (chronic) - systemic effects	89 mg/m <sup>3</sup> (Consumer) 500 mg/m <sup>3</sup> (Employee)

#### · PNECs

##### 67-63-0 propan-2-ol

PNEC, fresh water	140.9 mg/l (aquatic organism)
PNEC, marine water	140.9 mg/l (aquatic organism)
PNEC, fresh water sediment	552 mg/kg (aquatic organism)
PNEC, marine water sediment	552 mg/kg (aquatic organism)
PNEC, soil	28 mg/kg (terrestrial organism)

#### · 8.2 Exposure controls

##### · Personal protective equipment:

##### · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.

##### · Respiratory protection: Not required.

##### · Protection of hands:



If prolonged or repeated contact is likely, chemicalresistant gloves are recommended.

##### · Material of gloves Nitrile rubber, NBR

(Contd. on page 5)

GB

**Safety data sheet**  
according to 1907/2006/EC, as ammended by Regulation (EU) no.  
2015/830

Printing date 25.11.2020

Version: 1.0

Revision: 25.11.2020

(Contd. of page 4)

- **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Safety glasses

## SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:** Aerosol  
**Colour:** According to product specification

- **Odour:** Characteristic

- **pH-value:** Not applicable.

- **Change in condition**

**Melting point/freezing point:** Undetermined.  
**Initial boiling point and boiling range:** 154-193 °C

- **Flash point:** -97 °C

- **Flammability (solid, gas):** Not applicable.

- **Auto-ignition temperature:** 365 °C

- **Decomposition temperature:** Not determined.

- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

**Lower:** 0.7 Vol %  
**Upper:** 10.9 Vol %

- **Oxidising properties** No further relevant information available.

- **Vapour pressure at 20 °C:** 8,300 hPa

- **Density at 20 °C:** 0.68 g/cm<sup>3</sup>  
· **Evaporation rate** Not determined.

- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.

- **Partition coefficient: n-octanol/water:** Not determined.

- **Viscosity:**

**Dynamic:** Not determined.  
**Kinematic:** Not determined.

- **9.2 Other information** No further relevant information available.

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.

- **10.2 Chemical stability** Stable under recommended storage and handling conditions (see section 7).

- **10.3 Possibility of hazardous reactions**

Dangerous reactions are not expected if the product is handled according to its intended use.

- **10.4 Conditions to avoid** No further relevant information available.

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, as amended by Regulation (EU) no.  
2015/830

Printing date 25.11.2020

Version: 1.0

Revision: 25.11.2020

(Contd. of page 5)

- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No decomposition if used according to specifications.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics**

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>5,000 mg/l (rat)

**106-97-8 butane, pure**

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

**64742-95-6 Hydrocarbons, C9, aromatics**

Oral	LD50	2,000-5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

**67-63-0 propan-2-ol**

Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	13,900 mg/kg (rabbit)
Inhalative	LC50/6h	>25 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

**64742-95-6 Hydrocarbons, C9, aromatics**

EC50, acute	1-10 mg/l (algae)
-------------	-------------------

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, as ammended by Regulation (EU) no.  
2015/830

Printing date 25.11.2020

Version: 1.0



Revision: 25.11.2020

(Contd. of page 6)

### SECTION 13: Disposal considerations

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

· <b>14.1 UN-Number</b> · <b>ADR, IMDG, IATA</b>	UN1950
· <b>14.2 UN proper shipping name</b> · <b>ADR</b> · <b>IMDG</b> · <b>IATA</b>	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· <b>14.3 Transport hazard class(es)</b> · <b>ADR</b>	
	
· <b>Class</b> · <b>Label</b>	2 5F Gases. 2.1
· <b>IMDG, IATA</b>	
	
· <b>Class</b> · <b>Label</b>	2.1 2.1
· <b>14.4 Packing group</b> · <b>ADR, IMDG, IATA</b>	None. Void
· <b>14.5 Environmental hazards:</b>	Not applicable.
· <b>14.6 Special precautions for user</b> · <b>Hazard identification number (Kemler code):</b> · <b>EMS Number:</b> · <b>Stowage Code</b>	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· <b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.

(Contd. on page 8)

GB



**Safety data sheet**  
according to 1907/2006/EC, as amended by Regulation (EU) no.  
2015/830

Printing date 25.11.2020

Version: 1.0

Revision: 25.11.2020

(Contd. of page 7)

· **Transport/Additional information:**

· **ADR**

- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity
- **Transport category** 2
- **Tunnel restriction code** D

· **IMDG**

- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity

- **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

### SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

67-63-0 | propan-2-ol

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P3a** FLAMMABLE AEROSOLS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 9)



**Safety data sheet**  
**according to 1907/2006/EC, as ammended by Regulation (EU) no.**  
**2015/830**

Printing date 25.11.2020

Version: 1.0

Revision: 25.11.2020

(Contd. of page 8)

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*DNEL: Derived No-Effect Level (REACH)*

*PNEC: Predicted No-Effect Concentration (REACH)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Flam. Gas 1A: Flammable gases – Category 1A*

*Aerosol 1: Aerosols – Category 1*

*Press. Gas (Comp.): Gases under pressure – Compressed gas*

*Flam. Liq. 2: Flammable liquids – Category 2*

*Flam. Liq. 3: Flammable liquids – Category 3*

*Acute Tox. 3: Acute toxicity - inhalation – Category 3*

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

*Asp. Tox. 1: Aspiration hazard – Category 1*

*Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

GB