

Leather Filling Paste

Special flexible filling paste designed to cover scratches, holes or cracks on leather and synthetic leather, creating a soft, adhesive and flexible layer.

Also suitable for rubber midsoles.

Not suitable for suede and nubuck.



Surfaces to Repair



SMOOTH LEATHER



FAUX LEATHER



RUBBER

Description

Suitable for a wide variety of smooth and synthetic leather, and for rubber soles. Not suitable for suede and nubuck. It provides great filling and flexibility properties, successfully promoting fluidity and a perfect uniform finish.

Once the product has been applied, the final result hides all surface defects or scratches.

Dried paste can be painted with the desired color for a perfect and professional finish.

Colours



100
Neutro
Neutral



101
Blanco
White



107
Amarillo
Yellow



112
Rojo
Red



118
Negro
Black



122
Azul Eléctrico
Daphne



139
Marrón medio
Medium brown

How to use

1. Clean, degrease, brush to remove dust from all surfaces to be restored.
2. Apply with a brush, roller or a spatula the necessary thin layers to cover completely any holes or the scratches to be repaired.
3. Let it dry between layers for approximately one hour. It is important to not apply too much quantity of the product in each layer.
 - TIP 1:** If you want to cover holes, to achieve a better finish we recommend using silicone release paper as support to avoid adhesion and keep the paste firm.
4. Dilute the last layer with water to achieve a similar texture to the surface to be repaired. Apply it with a spatula or a cloth to avoid imperfections and to generate a smooth and homogeneous finish. Dried paste can be reactivated with the alcohol, can be corrected and textured for professional finish.
 - TIP 2:** To speed up the process a hairdryer can be used, however this needs to be very gently, at low temperature and 20 cm from the surface. We recommend to let it dry naturally.
5. Once the process is finished, let it dry for 12 hours to achieve a better mechanical properties.
 - TIP 3:** If the quantity of paste applied is excessive, this can be removed before painting in two different ways:
 - a. Sand gently with a very thin sandpaper
 - b. Carefully remove the remaining paste with ethyl alcohol.
6. Once the paste is completely dry, it can be painted for a perfect finish.
 - TIP 4:** Store between 5°C and 35°C, protect from heat, cold and frost.

