



6120 siafleece

For even surface finishes in manual and portable machine sanding



For even surface finishes in manual and portable machine sanding

6120 siafleece can be used for dry and wet sanding and impresses due to its high conformability, consistent performance over the entire lifetime, low tendency to clog, and consistently high surface quality.

- ▶ Highly flexible and adaptable to contours
- ▶ 3-dimensional grit penetration
- ▶ Low clogging
- ▶ Alkali- and solvent-resistant
- ▶ Extremely long lifetime
- ▶ Very low flammability and thus a safe alternative to steel wool
- ▶ For manual or portable machine sanding
- ▶ Suitable for general use in dry and wet sanding applications

Product profile

Grit type:	Aluminium oxide Silicon carbide
Grit range:	150
Backing:	Nonwoven
Coating:	Mechanical
Bonding:	Resin over resin

Use



Applications

- Keying of wood, composite materials, paint, lacquers and primer filler
- Sanding off raised wooden fibres
- Keying surfaces for better paint adhesion
- Fine sanding of surfaces
- Scuffing solid surface materials
- Removal of rust
- Removal of discolouration
- Structuring and finishing

Materials

Soft wood; Hard wood; Lacquer

Unalloyed / low-alloy steel; Non-ferrous metal; High-alloy steels

Technology

siafast